

## Addendum to the EWT-3900 Wireless Thermostat

*The Model EWT-3900 Wireless Thermostat is Linked to the Controller at the factory. Follow the instructions below only if you find the Thermostat and Receiver are not communicating.*

1. Make sure the thermostat is in the OFF position.
2. Mount the Receiver in the desired location.
3. Connect 24vac to the Receiver including all necessary HVAC equipment connections.
4. With the Thermostat in hand, Stand close to the Receiver and press the Matching Key on the side of the box for 1 second. Wait for three minutes. The thermostat will automatically link to the Receiver.
5. Test by selecting Fan ON in the thermostat screen. Wait for the radio signal icon to flash on the screen. The HVAC fan should energize.

*If the Linking or Matching is unsuccessful try pressing the Matching key again. If you are still unsuccessful, perform the following procedure:*

1. Make sure the thermostat is in the OFF position.
2. Press and Hold the PROG key for 3 seconds until the screen changes to the Menu screen.
3. Press the PROG key to scroll through the menu until the LCD screen displays CRES.
4. Use the UP key to select 1. Press the Matching Key on the Receiver and then press the center button between the Up and Down arrows on the Thermostat.
5. Wait for 30 seconds, the Thermostat will force the receiver to link.
6. Test by selecting Fan ON in the thermostat screen. Wait for the radio signal icon to flash on the screen. The HVAC fan should energize.

If you continue to have difficulty matching your thermostat to the Receiver, please contact the Engineering Dept. at EWC Controls, Inc. 1-800-446-3110.

